

Module	Model	Calendar (programmed to the year)	Illumination	Alarm	Hourly time signal	Snooze feature	Measuring unit (sec.)	Capacity (hours)	Split time	Stopwatch	Count-down timer	World time	Dual time	Date display	Battery life (years)	Battery type	Accuracy	Water-resistant to	Additional functions	Page	
1330	LTP-1165A-1C2EF; -2C2EF; -7C2EF	28 days for February	• (AUTO EL)	•	•	1/100	24	24	1/100	24	•	•	•	•	3	SR626SW	± 20	ISO 2281	Neobrite, screw lock back, weekday display	18/19	
	LTP-1284D-2AEF; -4AEF; -7AEF																				
	LTP-1287B-7B2EF; -7B3EF																				
	LTP-1287B-7B4EF; -7B6EF																				
	LTP-1288B-7B2EF; -7B3EF																				
	LTP-1288B-7B4EF; -7B9EF																				
1747	MTP-1165A-1C2EF; -2C2EF; -7C2EF	2099	• (LED)	•	•	1/100	12	12	1/100	24	•	•	•	•	2	SR521SW	± 20	ISO 2281	Neobrite, screw lock back	22	
	SHN-4003D-1FEF; -2FEF; -6FEF																				
	SHN-4003SP-7FEF																				
	SHN-4004D-1CEF; -4CEF; -6CEF; -7CEF																				
1966	W-754H-1AVEF; -2AVEF; -7AVEF	2099	• (LED)	•	•	1/100	1	1	1/100	24	•	•	•	•	10	CR2016	± 30	10 bar	Neobrite, screw lock back	23	
2328	EF-512D-1AVEF; -4AVEF																				
2364	MTR-301-1AVEF; -7AVEF																				
2672	LW-200-4BVEF; LW-200D-2AVEF	2099	• (LED)	•	•	1/100	1	1	1/100	24	•	•	•	•	10	CR1620	± 20	5 bar	Neobrite, screw lock back	20	
	2711																				EF-500D-1AVEF; -2AVEF; -7AVEF
	2719																				EF-513D-1AVEF; -5AVEF; -7AVEF
																					EF-125D-1AVEF; -2AVEF; -7AVEF
2783	MTR-100-1AVEF; -7AVEF	2099	• (EL)	•	•	1/10	24	24	1/10	24	•	•	•	3	SR626SW	± 20	5 bar	Neobrite, screw lock back	21		
3019	MTR-101-1AVEF; -7AVEF																				
3036	WV-M401DE-7ER	28 days for February	• (LED)	•	•	1/100	24	24	1/100	24	•	•	•	•	5	CR2025	± 30	ISO 2281	radio signal reception (EU, USA, Japan)	10	
	3037																				LDF-10-4AVEF; -7AVEF
	3039																				LDF-20-3AVEF; -4AVEF; -9AVEF
																					WV-M400DE-7ER
3074	W-110-1AVEF; -7AVEF	2099	• (LED)	•	•	1/100	24	24	1/100	24	•	•	•	5	CR2025	± 30	ISO 2281	radio signal reception (EU, USA, Japan)	23		
3794	LAQ-2000D-1AEF; -4AEF; -5AEF																				
	LAQ-2000L-1AEF; -7AEF		• (LED)	•	•	1/100	1	1	1/100	1	•	•	•	•	2	SR726WX2	± 30	ISO 2281	Button tone on/off	17	
																				17	